

Kodos Plus Normale

INDUSTRIAL LED HIGH BAYS



Lighting characteristics

Light intensity: > 95%
Lifespan (L80): 50,000 h (Tp: 60°)
Photobiological Risk Group RG0 ("Exempt") (EN 62471:2006)

Mechanical characteristics

Body in die-cast aluminium
Tempered glass shield
International Protection Class IP65
Shock Protection IK08 (EN60529)

Electrical characteristics

AC input: 85/265V - 50/60Hz
Power factor: >90

Lamp characteristics

SMD LED chip

CRI Ra>80

Accessories

Dimming 0-10V/DALI (sub-code D)
There is a shield complying with the HACCP regulation for food processing and transformation environments
A reinforced shield is also available

Regulations

Produced in accordance with EN standards EN55015:2013, EN61547:2009, EN61000-3-2:2006+A1:2009+A2:2009, EN61000-3-3:2013, EN61000-4-2:2009, EN61000-4-3:2006+A2:2010, EN61000-4-4:2004+A1:2010, EN61000-4-5:2006, EN61000-4-6:2009, EN61000-4-8:2010, EN61000-4-11:2004, EN 60598-1:2008+A11:2009, EN 62471:2008, EN 62031:2008, IEC62321:2013, EN60529:1992, EN 62262:2002, EN 12464-1.

	100W	150W	200W
H [mm]	549	459	467
L [mm]	246	303	246
D [mm]	367	367	367

CODE	POWER [W]	COLOUR [K]	EFFICIENCY [lm/W]
KP101245804	100	4500	120
KP101255804	100	5500	120
KP151245804	150	4500	120
KP151255804	150	5500	120
KP201245804	200	4500	120
KP201255804	200	5500	120

The data have a tolerance level of +/-10% and are subject to modification without prior notice.
The pictures and dimensional parameters are merely an indication, and may differ from the end product.

